

Lot 1 - Electronics

MM#	Item	Quantity	Description
21241928	Controller	1	COMPUTAPAK GP4 110V AC CONTROLLER Manufacturer: COMPUTAPAK Calibrated in August 2020 Condition: Used Model: SYSTEM 4X Serial No.: 55838 Cert. No.: T2532 Supply: 110V AC Dimension: 430MM x 260MM x 300MM Weight: 6.65kg
21240776	CPU	1	SPARE PART FOR PALLETISER M/C NO. 21765 CONTROL PANEL - CPU SLC 5/03 (12K) Manufacturer: SCHENK PROCESS UK LTD Condition: New Serial No. 58240224 Part No. 1747-L532 Manufacturing Date: 2017/11/09 Product of Singapore 500mA @ 5V DC 176mA @ 24DC Temperature Code: T3C (0 degrees to 60 degrees) Dimension: 140MM x 130MM x 40MM Box Dimension: 170MM x 250MM x 60MM Weight: 0.4kg
21242258	Motor Tachogenerator	2	MOTOR DC TACHOGENERATOR Manufacturer: INFRANOR MAVILOR CML-30 CL039.000.0009.A6 SE1907476 40W IEC 34-1 IP 54 Voltage: 14.8V RPM: 1000 Weight: 0.4kg Comes with Drilling Jig, wheel, O-Belt (PU)
21240888	Heater Temperature Controller	2	Controller Temperature Ropex RES-403 Manufacturer: Ropex Type: RES - 403 (400V AC) Serial no. : 703849 P/N: 740303 Manufacturing date: 11/2017 Made in Germany Dimensions: 170mm x 140mm x 90mm
21242148	Keypad	1	Keypad Simatic OP7 Manufacturer: Siemens Made in Germany Operator Panel: OP 7-PP S/N: 6AV3 607-1JC00-0AX1 Part no. 52057563 Input DC 24V / max 0.24A

7

Lot 2 - Gearmotors

MM	Vendor	Qty	Description
21241824	SEW- EURODRIVE, INC. USA	1	Type: DFW132S4BHG8 TEFC 3PH S.O: 850006277.01.01.001 Manufacturing year: 2001 HP: 7.5 HP RPM (in/out): 1430/38 Nominal frequency: 50Hz Voltage: 240/415Y Current: 18.4A/ 10.6A Brake: 24V, Torque 22.1 lb-ft, BSG Control Maximum Ambient: 40-C Shaft 50MM Mount T.B. 270DEG UNV Insulation Class: F NO HAND RELEASE ON BRAKE Dimensions: 800MM x 200MM x 30MM

Lot 2 - Gearmotors (Continued)

MM#	Vendor	Quantity	Description
21241817	Parsons Peebles Service LTD	2	GEARMOTOR (LAYER PUSHER) Vendor: Parsons Peebles Service LTD Type: R27 DRS71M4BE05 S.O: 30.173544450.1.0001.11 Manufacturing year 2011 HP: 0.75 HP RPM(in/out): 1380/181 Nominal frequency: 50Hz Voltage: 230V/400Y Current: 2.70A/ 1.55A Torque 29Nm Shaft B8 250MM Mount T.B. 270DEG UNV INS. F Dimensions: 500MM x 150MM x 240MM Weight: 15.825kg Age: 6 Months.
21241825	SEW- EURODRIVE, INC. USA	1	Type: DFT90S4BMS2 TEFC 3PH S.O: 880221198.00.00.001 HP: 1.5 HP Power: 0.75kW RPM(input): 1400 Nominal frequency: 50Hz Voltage: 240/415Y Current: 4.51A/ 2.6A Brake: 230V, Torque 14.8 lb-ft, BG1.5 Brake rectifier Maximum Ambient: 40-C Shaft Diameter: PIN14 35MM BORE H3 90DEG 1 FINS Flange Diameter: S57 Cable Entry: N Dimensions: 450MM x 250MM x 200MM
21241838	SEW- EURODRIVE, INC. USA	1	Type: DFT90S4BMS2 TEFC 3PH S.O: 850298857.01.01.001 Manufacturing year: 2001 HP: 0.5 HP RPM(in/out): 1380/68 Out Torque: 410 lb-ft Gear Ratio: 20.33 Nominal frequency: 50Hz Voltage: 240/415Y Current: 2.1A/ 1.2A Brake: 230V AC, Torque 1.8 lb-ft, BG1.5 Brake rectifier Maximum Ambient: 40-C Shaft Diameter: 30MM 30MM BORE F INS RH MT. POS H3 180DEG 1 TORQUE ARM A SIDE . 45DEG 3PH Mtg Position: H3 Insulation Class: F Cable Entry: 1 Dimensions: 550MM x 300MM x 200MM
21241826	SEW- EURODRIVE, INC. USA	1	Type: DFT80K4BMG05 TEFC 3PH S.O: 850165874.99.99.002 Manufacturing year: 2002 HP: 0.75 HP RPM(in/out): 1380/109 Nominal frequency: 50Hz Voltage: 240/415Y Current: 2.9A/ 1.7A Brake: 220V AC, Torque 1.8 lb-ft, BG1.5 Brake rectifier Maximum Ambient: 40-C Shaft Diameter: 20MM 20MM BORE H1 TORQUE ARM POS. B 270 DEG NORM Mtg Position: H3 Insulation Class: F Cable Entry: 1 Dimensions: 500MM x 250MM x 150MM
21241832	SEW- EURODRIVE, INC. USA	1	Type: DFT80K4BMG05 TEFC 3PH S.O: 850298847.01.01.001 Manufacturing year: 2001 HP: 0.75 HP RPM(in/out): 1380/25 Out Torque: 1290 lb-in Gear Ratio: 47.32 Nominal frequency: 50Hz Voltage: 240/415Y Current: 2.9A/ 1.7A Brake: 230V AC, Torque 1.8 lb-ft, BG1.5 Brake rectifier Maximum Ambient: 40-C Shaft Diameter: 25MM 25MM SHAFT 180DEG NORMAL SHAFT POSITION B

Lot 2 - Gearmotors (Continued)

MM#	Vendor	Quantity	Description
21241835	SEW- EURODRIVE, INC. USA	1	Type: DFT71D4 TEFC 3PH S.O: 850298856.01.01.001 Manufacturing year: 2001 HP: 0.5 HP RPM (in/out): 1380/68 Out Torque: 410 lb-in Gear Ratio: 20.33 Gear S.F.: 1.15 Nominal frequency: 50Hz Voltage: 240/415Y Current: 2.1A/ 1.2A Brake: 230V AC, BG1.5 Brake rectifier Maximum Ambient: 40-C Shaft Diameter: 30MM 30MM BORE 180DEG 1 TORQUE ARM A Mtg Position: H3 Insulation Class: F Dimensions: 400MM x 250MM x 200MM Mtg Position: B8B Insulation Class: F Dimensions: 500MM x 250MM x 200MM
21241833	SEW- EURODRIVE, INC. USA	1	Type: S57DT71C4BMG05 S.O: 850298851.01.01.001 HP: 0.33 HP RPM (in/out): 1380/16 Out Torque: 1300 lb-in Gear Ratio: 84 Gear S.F.: 1.0 Nominal frequency: 50Hz Voltage: 240/415Y Current: 1.35A/ 0.78A Brake: 230V AC, BG1.5 Brake rectifier Maximum Ambient: 60-C Shaft Diameter: 30MM 25MM SHAFT 180DEG NORMAL SHAFT POSITION B Mtg Position: V5B Insulation Class: F Dimensions: 460MM x 250MM x 150MM
21241834	SEW- EURODRIVE, INC. USA	1	Type: DFT71D4 TEFC 3PH S.O: 850298856.01.01.001 Manufacturing year: 2001 HP: 0.5 HP RPM (in/out): 1380/68 Out Torque: 410 lb-in Gear Ratio: 20.33 Gear S.F.: 1.15 Nominal frequency: 50Hz Voltage: 240/415Y Current: 2.1A/ 1.2A Brake: 230V AC, BG1.5 Brake rectifier Maximum Ambient: 40-C Shaft Diameter: 30MM 30MM BORE 180DEG 1 TORQUE ARM A Mtg Position: H3 Insulation Class: F Dimensions: 400MM x 250MM x 200MM

Lot 3 - Motors and Gearboxes

MM	Vendor	Qty	Description
22099381	SEW- EURODRIVE, INC. USA	1	Motor Serial number 30.1951862401.0001.14 Manufacturing year 2014 Speed [r/min] 1435 / 110 Total ratio [i] 13.08 Ma max [Nm] 165 Output torque [Nm] 65 Service factor SEW-FB 2,50 Mounting position M1B Connection type 016 ISO code CLP 220 Lubricant type Miner.Oil Lubricant volume [l] 0,50 Motor power [kW] 0.75 Motor frequency [Hz] 50 Cyclic duration factor S1-S10 S1 Motor voltage [V] / conn. type 400 star Rated current [A] 1,68 cos phi 0,79 Thermal cl.[°C]/Enclosure[IP] 130(B) / 54 International efficiency class IE2 Efficiency (100% Pn) [%] 81,0 Design specification 001 Ambient temperature min. [°C] -20 Ambient temperature max. [°C] 40 Brake voltage [V]/-torque [Nm] 230 AC / 10 Brake rectifier nameplate BGE1.5SR Nameplate English Weight 30.00 kg Dimension 560mm x 250mm x 210
21240970	SEW- EURODRIVE, INC. USA	1	Motor Serial number 30.1768009701.0001.12 Manufacturing year 2012 Speed [r/min] 1435 / 23 Total ratio [i] 63,30 Ma max [Nm] 400 Output torque [Nm] 315 Service factor SEW-FB 1,25 Mounting position M5A Connection type 1 ISO code CLP 220 Lubricant type Miner.Oil Lubricant volume [l] 1,60 Motor power [kW] 0.75 Motor frequency [Hz] 50 Cyclic duration factor S1-S10 S1 Motor voltage [V] / conn. type 230/400 delta/star Rated current [A] 2,90 / 1,68 cos phi 0,79 Thermal cl.[°C]/Enclosure[IP] 130(B) / 54 International efficiency class IE2 Efficiency (100% Pn) [%] 81,0 Design specification 1 Ambient temperature min. [°C] -20 Ambient temperature max. [°C] 40 Brake voltage [V]/-torque [Nm] 230 AC / 10 Brake rectifier nameplate BG1.5 Nameplate (sets per unit) 1 set of nameplates Nameplate English / Laser stainless steel Part number 1st nameplate 1885782 Weight 34.00 kg Dimension 600mm x 230mm x 200mm

Lot 3 - Motors and Gearboxes (Continued)

MM	Vendor	Qty	Description
21240963	SEW- EURODRIVE, INC. USA	1	Brand New Motor Serial number 30.7162676101.0001.14 Manufacturing year 2014 Speed [r/min] 1360 / 77 Total ratio [i] 17,62 Ma max [Nm] 110 Output torque [Nm] 60 Service factor SEW-FB 1,85 Mounting position M1B Connection type 1 ISO code CLP 680 Lubricant type Miner.Oil Lubricant volume [l] 0,40 Motor power [kW] 0.55 Motor frequency [Hz] 50 Cyclic duration factor S1-S10 S1 Motor voltage [V] / conn. type 230/400 delta/star Rated current [A] 2,70 / 1,55 cos phi 0,72 Thermal cl.[°C]/Enclosure[IP] 130(B) / 54 Efficiency (100% Pn) [%] 70,6 Design specification 1 Ambient temperature min. [°C] -20 Ambient temperature max. [°C] 40 Brake voltage [V]/-torque [Nm] 230 AC / 10 Brake rectifier nameplate BGE1.5 Nameplate English Weight 23.00 kg Dimension 470mm x 160mm x 260mm
21240964	SEW- EURODRIVE, INC. USA	1	Motor Serial number 30.1733389901.0001.11 Manufacturing year 2011 Speed [r/min] 1435 / 101 Total ratio [i] 14,24 Ma max [Nm] 110 Output torque [Nm] 63 Service factor SEW-FB 1,75 Mounting position M1B Connection type 1 ISO code CLP 680 Lubricant type Miner.Oil Lubricant volume [l] 0,40 Motor power [kW] 0.75 Motor frequency [Hz] 50 Cyclic duration factor S1-S10 S1 Motor voltage [V] / conn. type 230/400 delta/star Rated current [A] 2,90 / 1,68 cos phi 0,79 Thermal cl.[°C]/Enclosure[IP] 130(B) / 54 International efficiency class IE2 Efficiency (100% Pn) [%] 81,0 Design specification 1 Ambient temperature min. [°C] -20 Ambient temperature max. [°C] 40 Brake voltage [V]/-torque [Nm] 230 AC / 10 Brake rectifier nameplate BGE1.5SR Nameplate (sets per unit) 1 set of nameplates Nameplate English / Laser stainless steel Part number 1st nameplate 1885782 Weight 27.00 kg Dimension 500mm x 220mm x 200mm

Lot 3 - Motors and Gearboxes (Continued)

MM	Vendor	Qty	Description
21240969	SEW- EURODRIVE, INC. USA	1	Motor Serial number 30.1781516701.0001.12 Manufacturing year 2012 Speed [r/min] 1435 / 133 Total ratio [i] 10,80 Ma max [Nm] 109 Output torque [Nm] 48 Service factor SEW-FB 2,30 Mounting position M1A Connection type 1 ISO code CLP 680 Lubricant type Miner.Oil Lubricant volume [l] 0,40 Motor power [kW] 0.75 Motor frequency [Hz] 50 Cyclic duration factor S1-S10 S1 Motor voltage [V] / conn. type 230/400 delta/star Rated current [A] 2,90 / 1,68 cos phi 0,79 Thermal cl.[°C]/Enclosure[IP] 130(B) / 54 International efficiency class IE2 Efficiency (100% Pn) [%] 81,0 Design specification 1 Ambient temperature min. [°C] -20 Ambient temperature max. [°C] 40 Brake voltage [V]/-torque [Nm] 230 AC / 10 Brake rectifier nameplate BGE1.5 Nameplate (sets per unit) 1 set of nameplates Nameplate English / Laser stainless steel Part number 1st nameplate 1885782 Weight 26.00 kg Dimension 200mm x 230mm x 200mm
21241658	SEW- EURODRIVE, INC. USA	1	Motor Gear Catalog designation DFT90S4BMG2 Serial number 850238069.09.09.001 Manufacturing year 2001 Mounting position M4 Shaft diameter PIN14 Flange diameter S57 Terminal box position 90 Cable entry at terminal box X Motor power 1.5 Motor voltage 240V/415Y Frequency 50 Wiring diagram DT13 Rated current 4.51/2.6 KVA Code F Thermal class F Brake rectifier BG1.5 Brake voltage 220AC Other Special Volt/Freq. CB@90, CE X Weight on request Dimension 380mm x 300mm x 200mm
21241010	SEW- EURODRIVE, INC. USA	1	Motor Gear Serial number W797364 Mounting position H1A Motor power (KW) 0.75 Motor voltage 230V/400Y Frequency 50 RPM 20 Ratio 69.35 Rated current 3.7/2,1 Insulation Class B Brake Torque (Nm) 10 Brake voltage 230 Weight on request Dimension 380mm x 300mm x 200mm
21241009	SEW- EURODRIVE, INC. USA	1	Motor Gear Serial number W797365 Mounting position B3B Motor power (KW) 1.5 Motor voltage 230V/400Y Frequency 50 RPM 138 Ratio 15.85 Rated current 6.2/3.55 Insulation Class B Brake Torque (Nm) 20 Brake voltage 230 Weight on request Dimension 570mm x 270mm x 220mm

Lot 3 - Motors and Gearboxes (Continued)

MM	Vendor	Qty	Description
21241008	SEW- EURODRIVE, INC. USA	1	Motor Gear Serial number W797366 Mounting position B8B Motor power (KW) 1.1 Motor voltage 230V/400Y Frequency 50 RPM 88 Ratio 15.85 Rated current 4.9/2.8 Insulation Class B Brake Torque (Nm) 20 Brake voltage 230 Weight on request Dimension 380mm x 300mm x 200mm
21242153	SEW- EURODRIVE, INC. USA	1	Motor Gearbox Serial number 30.0126090101.0001.04.01 Manufacturing year 2001 Input speed [r/min] 280 - 1 Output speed [r/min] 89.0 - 446.0 Total ratio [i] 3,14 Output torque [Nm] 32 Service factor SEW-FB 2,00 Mounting position M2 ISO code CLP 220 Lubricant volume [l] 0,80 Motor power [kW] 0.3 / 1.5 Motor frequency [Hz] 50 Cyclic duration factor S1-S10 S1 Multi range-voltage 50Hz [V] 380-500 Multi range-voltage 60Hz [V] 380-500 MM rated main current [A] 3,50 Thermal class/Enclosure[IP] F / 54 protection type 0 / 0 Ambient temperature motor [°C] -25 BIS +40 Brake type+size BMG2 Brake voltage [V]/-torque [Nm] 230 AC / 20 Multi range-voltage brake [V] 230 AC Brake rectifier nameplate None Weight 35.00 kg Dimension 530mm x 330mm x 200mm
21239339	Seipee	2	Motor (Gearbox + Vari Speed) Made in Italy Serial number MOT. 3 No. E 10/19AZ 90L A/4 Mounting position B8B Motor power (KW) 1.5 Motor voltage 240V/415Y Frequency 50 RPM 1420 Ratio 15.85 Rated current 6.3/3.65 Insulation Class F Brake Torque (Nm) (AC4) 20 Nm Brake voltage 415 Weight 15kg Dimension 750mm x 230mm x 250mm
21240833	Varvel	2	Gearbox Type FRC220/B7 Serial number B09049700168 Lubricated for life Gears only Weight 11.74kg Dimension 240mm x 200mm x 170mm

14

Lot 4 - Pneumatics

MM	Item	Qty	Description
21240746	Air Cylinders	2	Cylinder Air - spare part for slipsheet dispenser Manufacturer: Simon Richard Part No. SCM063 Max working pressure: 10 bar Dimension: 1050mm (length) x 177mm
21240737	Air Cylinder	1	Cylinder Air - spare part for slipsheet dispenser P130/S/20 Dimension: 1450mm (length) x 40mm

Lot 4 - Pneumatics (Continued)

MM	Item	Qty	Description
21241977	Motor C/W Vacuum Pump	1	Dry running vacuum pump (NEW) Manufacturer: Gardner Denver 2006/42/EC Series: V-VTN-41 (01) 1,50S1A3MG Serial no. SC10349178002 Part no. 1028510113 Power: 1.5KW Voltage: 440V RPM: 1370 Dimension: 580mm x 300mm x 750mm
21240746	Pneumatic Actuator	2	Manufacturer: Actrea ASR 500 Pressure Max: 150psi/10 bar Dimension: 400mm x 180mm x 200mm Weight: 16.78kg

6

Lot 5 - Printing Items

MM	Item	Qty	Description
21242234	Ink Jets	3 Boxes	5009 BLACK INK - MARKEM IMAJE LTD 3 boxes of INK for MARKEM 5000 series printers. The boxes come with 6 packs of 5009 Black Ink each. Condition: New Description: 5009 Black Serial No.: US19370122, US19500067, US19390020 Part No.: 8028210 Expiry Date: Sept/2024 Box dimension: 320MM x 185MM x 215MM Volume per pack: 1000 CM^3
21242239	REFURBISHED Print Head	3	MARKEM 5200 PRINthead EXCHANGE P/n: 0828766 Model No: ENR0829033 (GS20330078) ENR0825200 ENR0825400 The print head can only be used with the above models together. Dimension: 140MMx 130MM x 105MM Weight: 2.2kg

6

Lot 6 - Rollers

MM	Item	Qty	Description
21242021	Roller	1	Dimension: 130mm (diameter) x 550mm
21240782	Roller drive with bearings	1	METTLER TOLEDO LTD SPARE PART FOR GARVENS V040 CHECK WEIGHER SER. NO. 19978 - DRIVE ROLLER COMPLETE ASSEMBLY WITH BEARINGS BALANCED M000048-BV3 PART N Part no. 24200764
21240832	Roller Driven	11	Part no. 078366906 Dimension: 100mm (diameter) x 140mm
21241287	Roller prestretch	2	ITW MIMA SERVICES SPARE FOR OCTOPUS 2100 BTS -PRE-STRETCH ROLLER Part no. 01815800 Dimension : 40mm (diameter) x 600mm
21241701	Roller Assembly	2	Live Layer Forming Manufacturer: MOLLERS NORTH AMERIA INC LAYER FORMING LIVE ROLLER ASSEMBLY (BELT DRIVE) FOR PFS RIGHT ANGLE 950-01-320-4-003 ON LFLR CONV Dimension: 80mm (diameter) x 1550mm
21241288	Roller prestretch	1	ITW MIMA SERVICES SPARE FOR OCTOPUS 2100 BTS -PRE-STRETCH ROLLE Part no. 104043 Diameter: 80mm. Length: 679mm

17

SELLER DOES NOT BIND ITSELF TO AWARD A SALES AGREEMENT TO THE HIGHEST BIDDER. GOODS BEING OFFERED FOR SALE MAY NOT NECESSARILY BE AWARDED FOR SALE AFTER THE SUBSEQUENT ANALYSIS OF BIDS. SELLER RESERVES THE RIGHT TO WITHDRAW ANY ITEM FROM THE LOT ON OFFER.

IRG-20-145

SED 17580-17585