

Korsakov, Sakhalin Island, Russia
IRG-17-050
OCTG Drilling Equipment

Seq	Type	Joints	Size	Wt	Grade	Description	Comments
1	Screen	11	6 5/8	24.00	L80 1Cr	HYDRIL 521 BOX X PIN RANGE 3 CONTAINER (ENL SUPPLIED BASE PIPE), WITH RESLINK LINE SLOT SINGLE WIRE WRAPPED SAND SCREEN, WIRE: UNS S31603 (6.2 MM X 3.2 MM AXIAL AND 4.0 MM X 3.0 MM WRAPPING WIRE), SLOT OPENING: 225 MICRON. WELD TYPE STOP COLLARS - 3 PER ASSEMBLY ON BOX & PIN END PLUS 1 WEATHERFORD STOP COLLAR INSTALLED ON FAR PIN END (SLB SUPPLIED 2 x 8.125" SPIRALIZER CENTRALIZERS AND 1 WEATHERFORD STOP COLLAR). QUALITY PLAN, DR# KSB-64-16	Jts
2	Float Shoe	1	18 5/8	-	-	BUTTRESS THD. DAVIS-LYNCH DOUBLE VALVE UP-JET TAG-IN FLOAT SHOE, TYPE 502-DV-TLP-PVTS WITH LATCH-DOWN RECEPTACLE, TO BE RUN ON 87,50#, GRADE K-55 CSG, DR# YUZ-05-16	Assembly
3	Casing	1	18 5/8	87.50	J55N	BTC, DR# YUZ-05-16	
4	Pup Joint	1	4 1/2	12.75	-	TSH CS, 3m DR# KSB-67-16	
5	SGM-FS Assembly	1	4 1/2	12.75	-	SGM-FS ASSY, NPQG/NHQG/NMQG, SINGLE, TUBING, 4130/4140[80], QCP-10063261 DR# KSB-67-16	Assembly
6	Pup Joint	1	4 1/2	12.75	-	TSH CS, 2m DR# KSB-67-16	
7	Pup Joint	1	4 1/2	12.75	-	TSH CS, 3m DR# KSB-67-16	
8	Nipple	1	-	-	-	4.5in X 3.813in X NIPPLE Profile, DR# KSB-67-16	Assembly
9	Pup Joint	1	4 1/2	12.75	-	TSH CS, 2m, DR# KSB-67-16	
10	Pup Joint	1	4 1/2	-	L80	TSH Integral Pup Jt 3m, DR# KSB-65-16	
11	THT Hydraulic Set	1	-	26.00	-	THT Hydraulic-Set, Production Packer, 7 in., 26-32 lb/ft Weight Range, 5.875 in. Max OD, 3.860 in. Min ID, 68.79 in. Length, 9Cr-1Mo Matl, 80000 psi Min Yield, Nitrile rubber Element Matl, 4 1/2-12.75 TSH CS Box x Pin, 40-325 Deg. F, H2S/ CO2 Service, 6830 psi Pressure Rating, 212THT7058-CHAA, 102284286, DR# KSB-65-16	Assembly
12	TSH Integral Pup	1	4 1/2	12.75	L80	TSH Integral Pup Jt 2m, DR# KSB-65-16	
13	Tubing	1	4 1/2	12.75	-	TSH CS, Range 2 Tubing, DR# KSB-68-16	
14	Pump Out Plug	1	4 1/2	12.75	-	PUMP OUT PLUG, 4-1/2", 12.75PPF HYD-CS, BOX, ALLOY, WIRELINE RE-ENTRY GUIDE, XOM HPP, MFR: HALLIBURTON, DR# KSB-68-16	Assembly
15	Tubing	4	4 1/2	12.75	-	TSH CS, 9.75m, DR# KSB-68-16	-
16	Control Linr	1	1/4	0.049	-	1/4 in. OD x 0.049 in. WT, 1-825 w/ Santoprene 11mm x 11mm TEC w/ metal Spool, (4500 m), DR# YUZ-06-16	-
17	Tubing	1	-	-	-	NMQG-BA-LT, SINGLE - TUBING, EDMC-R, LOW TEMP CALIBRATION, DR# YUZ-06-16	-
18	Casing	1	10 3/4	60.70	L-80 1Cr	VamTop KX R3 Joints PAL 2 / CTP 2, DR# KSB-66-16	
19	Xover	1	10 3/4	60.70	L-80 1Cr	Vam Top KX box x 9.625", 47.00 lb/ft, Tenaris-Hydril W563 pin x 1.5 m long (+/- 7.6 cm) PAL 1, CTP2, DR# KSB-66-16	Assembly
20	Casing	2	13 3/8	68.00	-	Hydril 523. Average joint length 42.01 ft., DR# KSB-66-16	Loose
21	Pup Joint	1	10 3/4	60.70	L80	Vam Top KX box (coupling) x pin x 20 ft long (+/- 3") PAL 2, CTP2, DR# KSB-69-16	Loose
22	Casing	1	10 3/4	60.70	L-80 1Cr	VamTop KX R3 Joints PAL 2 / CTP 2 (Signed Landing Joint), DR# KSB-69-16	Loose
23	Pup Joint	1	10 3/4	60.70	L80	Vam Top KX box (coupling) x pin x 10 ft long (+/- 3") PAL 2, CTP2, DR# KSB-69-16	Loose
24	Pup Joint	1	9 5/8	47.00	P110	Tenaris-Hydril W563 box (coupling) x pin x 20 ft long (+/- 3") PAL 3, CTP2, DR# KSB-69-16	Loose
25	Casing	2	5 1/2	20.00	L-80 1Cr	Vam Top HC, L-80 1% Cr, R 3, PAL 1, CPT 2., DR# KSB-70-16	Loose
26	Casing	2	16	84.00	L80	R3 TENARIS-HYDRIL 521 SEAMLESS STEEL CASING PAL 2, CTP 2, DR# KSB-70-16	Loose
27	Centralizer	11	-	-	-	CENTRALIZER, BOW SPRING MODEL RC113 9-5/8 STRAIGHT SLIP-ON LAP-WELDED ROTATING WITH 6036095 STOP COLLAR INSIDE, 3/16 X 5 END BANDS, WITH 36R BOWS 13.375 OD, CARBON STEEL, DR# KSB-71-16	Package
28	Casing	1	18 5/8	87.50	J55N	J-55N, BTC, Range 3, ERW, CUT OFF - 18 5/8" BTC Pin x Pin full length joints	Loose
29	Casing	3	18 5/8	87.50	J55N	BTC, Range 3, ERW, CUT OFF - 18 5/8" BTC Pin x blank end	Loose
30	Casing	3	18 5/8	87.50	J55N	BTC, Range 3, ERW, CUT OFF - 18 5/8" blank end x blank end	Loose
31	Casing	1	18 5/8	87.50	J55N	BTC, Range 3, ERW, CUT OFF - 18 5/8" BTC Box (damaged) x blank end	Loose
32	Casing	12	13 3/8	72.00	P110	VAM SLIJ-II, special drift 12.25", R3 joint (11.58m per joint), DR# KSB-72-16	Loose
33	Casing	10	13 3/8	72.00	P110	VAM SLIJ-II, special drift 12.25", R3 joint (11.58m per joint), DR# KSB-72-16	Loose
34	Casing	3	13 5/8	72.00	P110	SEAMLESS, VAM TOP KX, CONNECTIONS, BOX X PIN, RANGE 3 LENGTH, DR# KSB-73-16	Loose
35	Casing	7	13 5/8	72.00	P110	SEAMLESS, VAM TOP KX, CONNECTIONS, BOX X PIN, RANGE 3 LENGTH, DR# KSB-74-16	Loose
36	Casing	2	13 5/8	72.00	P110	SEAMLESS, VAM TOP KX, CONNECTIONS, BOX X PIN, RANGE 3 LENGTH, DR# KSB-77-16	Loose
37	Casing	3	18 5/8	87.50	J55N	BTC, Range 3, ERW, DR# KSB-75-16	Loose
38	Casing	2	7	26.00	P110HC	SEAMLESS, HYDRIL-521 CONNECTIONS, BOX X PIN, RANGE 3 LENGTH., DR# KSB-76-16	Loose
39	Casing	3	18 5/8	87.50	J55N	NORMALIZED, SMLS, BTC API BOX X PIN, DR# CWS-008-12	Loose
40	Float Shoe	1	18 5/8	87.50	-	FLOAT SHOE 18-5/8"; OD BUTTRESS THD. DAVIS-LYNCH DOUBLE VALVE UP-JET TAG-IN, TYPE 502-DV-TLP-PVTS WITH LATCH-DOWN RECEPTACLE, TO BE RUN ON 87,50#, GRADE K-55 CSG, COMPLETE W/LATCH-DOWN WIPER PLUG FOR 5-7/8" 26,3LB GRADE S-135, XT-57 DRILL PIPE, DR# CWS-009-12	Assembly
41	Casing	1	18 5/8	87.50	-	NORMALIZED, SMLS, BTC API BOX X PIN, DR# CWS-009-12 / DR#CWS-014-12	