



# 880PG SERIES



## 880PG HYDRAULIC UTILITY CHAIN SAW

If you're looking for the highest level of performance and cutting capability, look no further. The 880PG hydraulic utility chain saw offers cutting depths up to 25" in ductile iron, cast iron, PVC, HDPE, Insituform lining and even Asbestos\* concrete pipe. The deep cutting ability of the 880PG with PowerGrit utility chain, allows the operator to make a single cut from one side meaning less excavation is required. Change the way you cut pipe! Also the 880PG is capable of operating the full line of 880F4 ProFORCE™ concrete cutting chains, meaning you can use the saw on masonry, stone, and even reinforced concrete - perfect for pipe taps, utility vaults, bridge work, and other utility applications.



\* Asbestos is a hazardous material, known to cause serious respiratory diseases. Cutting into asbestos can release asbestos fibers into the air. Always research and follow the correct safety procedures, including applicable national and state or provisional occupational health and safety regulations, and protect yourself and those around you from asbestos-related disease. Always arrange for the material to be removed safely by a qualified person. ICS is not responsible for exposure to asbestos caused by use of this product.

### 880PG PRODUCT SPECIFICATIONS - 8 GPM

<b>WEIGHT</b>	27.3 lbs (12.4 kg) with 15-inch (38 cm) bar and chain
<b>BAR LENGTH</b>	Up to 25 in (63 cm)
<b>MOTOR SPEED</b>	6100 rpm
<b>POWERHEAD DIMENSIONS</b>	23 in (58.5 cm) length 10.5 in (26.5 cm) height 9.5 in (24 cm) width
<b>TORQUE</b>	122 in-lbs (13.8 Nm)
<b>HORSEPOWER</b>	11.5 hp (8.6 kW)
<b>HYDRAULIC SUPPLY</b>	8 gpm (30 lpm), 2500 psi (172.5 bar)
<b>NOISE LEVEL</b>	98 dB @ 3 ft (1 m) (Sound pressure level) 107 dB @ 3 ft (1m) (Sound power level)
<b>VIBRATION LEVEL</b>	2.0 m/second <sup>2</sup> (front handle) 6.0 m/second <sup>2</sup> (rear handle)
<b>WATER SUPPLY</b>	Minimum 20 psi (1.5 bar)

*Product data shown is rated based on maximum input conditions and efficiency assumptions and may vary dependent on power supply.*

### 880PG PRODUCT SPECIFICATIONS - 12 GPM

<b>WEIGHT</b>	27.3 lbs (12.4 kg) with 15-inch (38 cm) bar and chain
<b>BAR LENGTH</b>	Up to 25 in (63 cm)
<b>MOTOR SPEED</b>	6500 rpm
<b>POWERHEAD DIMENSIONS</b>	23 in (58.5 cm) length 10.5 in (26.5 cm) height 9.5 in (24 cm) width
<b>TORQUE</b>	170 in-lbs (19.2 Nm)
<b>HORSEPOWER</b>	17.5 hp (13 kW)
<b>HYDRAULIC SUPPLY</b>	12 gpm (45 lpm), 2500 psi (172.5 bar)
<b>NOISE LEVEL</b>	98 dB @ 3 ft (1 m) (Sound pressure level) 107 dB @ 3ft (1 m) (Sound power level)
<b>VIBRATION LEVEL</b>	2.0 m/second <sup>2</sup> (front handle) 6.0 m/second <sup>2</sup> (rear handle)
<b>WATER SUPPLY</b>	Minimum 20 psi (1.5 bar)

*Product data shown is rated based on maximum input conditions and efficiency assumptions and may vary dependent on power supply.*



powergrit.com

