



MANUFACTURER: TIANJIN PIPE (GROUP) CORPORATION
ADD: JINTANG ROAD DONGLI DISTRICT, TIANJIN, CHINA

TEL: 86-22-24801073
FAX: 86-22-24801291

QUALITY CERTIFICATE

Licence No.:

QR-11-8.2.4-3

Contract No.

TPCO-14805E

L/C No.

Esso Exploration and Production Chd. Inc. Product CASING

Steel grade N80Q

O.D. x W.T. 71N 23.00LB/FI (177.80mm x 8.03mm) Packing IN LOOSE

Total pieces 820

Order P.O. No. 4501070019120 - Nov-2014

Manu. method HOT ROLLING SEAMLESS

Total metres

Standard API SPEC 5CT 9th

Length range 11-13M

Total Tons 356.765

Heat No.	Lot No.	Quantity				Delivery condition	Sample No.	Tensile test(MPa)						Impact test(J)										
		Pieces	Meters	Bundles	Tons			I* ℃	Tem. ℃	T.S.	Type	Y.S.	Elong. %	Shrink %	2* ℃	Size	AK1 %	Shear %	AK2 %	Shear %	AK3 %	Shear AVE %		
047230	82	186			81.069	Q+T	82-001-2	A	21	793	Rt0.5	679	24.0	A	0	10*5	65	100	59	100	61	100	62	100
047231	81	198			86.244	Q+T	81-001-1	A	23	755	Rt0.5	638	23.0	A	0	10*5	68	100	70	100	69	100	69	100
047231	82	118			51.464	Q+T	82-001-2	A	23	775	Rt0.5	656	22.0	A	0	10*5	76	100	74	100	72	100	74	100

Total		502																						
Heat No.		Lot No.	Sample No.	Hardness test (inside)			Hardness test (middle)			Hardness test (outside)			A: strip, L, bo=25.4mm Lo=50mm			A: V8/L								
			MAX	1	2	3	AVE	1	2	3	AVE		Thin	Thick	Thin	Thick	Thin	Thick	Thin	Thick	Thin	Thick	Thin	Thick

047230	82	82-001-2																						
047231	81	81-001-1																						
047231	82	82-001-2																						

WITNESSED
C-4174 DATE: 2014-02-09
SIGNATURE

Heat No.		Chemical composition % (L: Ladle analysis P: Product analysis)																Drift				NDE				Hydro. Test	
		Material	C	Si	Mn	P	S	Ni	Cr	Mo	Cu	Al	V	Pb	Sn	As	Sb	Bi	φ(mm)								

047230		L	0.29	0.24	1.27	0.011	0.003	0.04	0.05	0.01	0.07	0.016	0.01	0.0001	0.0034	0.0058	0.0017	0.0008	159.12		EMI+UT		5800PSI/8S			
30Mn5		P	0.31	0.24	1.26	0.012	0.005	0.03	0.09	0.02	0.05	0.013	<0.01	<0.001	0.0058	0.0066	<0.002	<0.001			F3+U3					
		P	0.31	0.24	1.26	0.012	0.005	0.03	0.09	0.02	0.05	0.012	<0.01	<0.001	0.0058	0.0065	<0.002	<0.001								
047231		L	0.29	0.24	1.27	0.011	0.003	0.03	0.05	0.01	0.05	0.018	0.01	0.0001	0.0030	0.0054	0.0014	0.0009	159.10		EMI+UT		5800PSI/8S			
30Mn5		P	0.32	0.25	1.25	0.012	0.005	0.03	0.09	0.02	0.05	0.012	<0.01	<0.001	0.0056	0.0066	<0.002	<0.001			F3+U3					
		P	0.32	0.24	1.25	0.013	0.005	0.03	0.09	0.02	0.05	0.012	<0.01	<0.001	0.0055	0.0066	<0.002	<0.001								
047231		L	0.29	0.24	1.27	0.011	0.003	0.03	0.05	0.01	0.05	0.018	0.01	0.0001	0.0030	0.0054	0.0014	0.0009	159.00		EMI+UT		5800PSI/8S			
30Mn5		P	0.32	0.25	1.25	0.012	0.005	0.03	0.09	0.02	0.05	0.012	<0.01	<0.001	0.0056	0.0066	<0.002	<0.001			F3+U3					
		P	0.32	0.25	1.25	0.012	0.005	0.03	0.09	0.02	0.05	0.012	<0.01	<0.001	0.0056	0.0066	<0.002	<0.001								
		P	0.32	0.24	1.25	0.013	0.005	0.03	0.09	0.02	0.05	0.012	<0.01	<0.001	0.0055	0.0066	<0.002	<0.001								

NDE (100%)		Visual and dimension	G	Pipe end NDE	G	Drift	G	Collapse test	SSC	HIC	We hereby state that all pipes are manufactured and inspected according to above standards and order.														Seal for certification:	
G																									A04	

Note:		No.	Page	(2)		Date: 2015-2-11																				Seal for certification:	

Remark: desti.=destination; tem.=temperature; speci.= specification; Manu.=Manufacture; G=Good; Hydro.=hydraulic

(FOR EXPORT ONLY)



Licence No.:

TEL: 86-22-24801073
FAX: 86-22-24801291

NO.: 14123053

[illegible]

Remark: desti. = destination; tem. = temperature; speci. = specification; Manu. = Manufacture; G = Good; Hydro. = hydraulic

(FOR EXPORT ONLY)



QUALITY CERTIFICATE

Licence No.:

TEL: 86-22-24801073
FAX: 86-22-24801291

NO. 14123054

[illegible]

Remark: desti. = destination; tem. = temperature; speci. = specification; Manu. = Manufacture; G = Good; Hydro. = hydraulic

(FOR EXPORT ONLY)

NO.: 15012965

Packing IN LOOSE

Steel grade N80Q

Manu. method HOT ROLLING SEAMLESS

Length range 12.00-13.00M

Tensile test(MPa)

(b) (7)(D) near identical

Type Y.S.

Rt0.5 684

 $L_{bo}=25.4\text{mm}$ Lo

Hardn

AVE	1
-----	---

	-
	*
	*
	6
	4

P: Product analysis

Al V

0.011	0.01	0.
-------	------	----

0.013	0.01	<
-------	------	---

0.012	0.01	∇
-------	------	----------

SSC	se test
-----	---------

Good; Hydro. = hydro.

(FOR EXPORT ONLY)