


SPECIFICATIONS

1. TANK — A. THEORETICAL SHELL FULL CAPACITY:
   COMPARTMENT 1 – 7,586 GAL
   COMPARTMENT 2 – 4,198 GAL
   COMPARTMENT 3 – 4,198 GAL
   COMPARTMENT 4 – 7,586 GAL
   B. CLASS BUILT DOT 111A100W1
   C. CLASS STENCIL – AAR 211A100W1
   D. SHELL AND HEAD MATERIAL – A516-70
   E. HEADS – 2:1 ELLIPTICAL, 7/16" THICK, 99 7/8" OD
   F. SHELL – 99" ID, 7/16" THICK
2. COIL — EXTERIOR SERPENTINE SYSTEM, 8 LINES, 8" COIL
3. UNDERFRAME — STUB SILL DESIGN WITH LIFT PROVISION
4. JACKET — ASTM A569 SHEET
   A. 107 7/8" ID
   B. SHELL AND HEAD THK – 11 GA
5. INSULATION — 4" GLASSWOOL BLANKET AT 1 LB DENSITY
6. TRUCKS — 100 TON, BARBER S-2D
   A. JOURNALS – 6 1/2" X 12", AAR APPROVED ROLLER BEARINGS
   B. WHEELS – AAR H-36 OR CH-36, CLASS "C", 1 WEAR
   C. SPRINGS – AAR D-5 (3 11/16" TRAVEL)
   D. BLOCK TYPE SIDE BEARINGS
7. DRAFT EQUIPMENT — 24 5/8" DRAFT GEAR POCKET
   A. COUPLERS – AAR SE60DE
   B. COUPLER YOKES – AAR SY40AE
   C. DRAFT GEAR – AAR M-901E
8. AIRBRAKE — TRUCK MOUNTED BRAKE EQUIPMENT WITH 8" CYLINDER, AUTOMATIC SLACK ADJUSTER, DOUBLE ACTING:
   A. BRAKE BEAMS – AAR #24
   B. BRAKE SHOES 2" HIGH FRICTION COMPOSITION, AAR #H 4
   C. PISTON TRAVEL – REGULATED AT 3"
9. HANDBRAKE — AAR APPROVED VERTICAL WHEEL UNIT WITH AAR SHEAVE WHEEL
10. GRATING — AAR APPROVED, STEEL
11. HANDRAIL — 1 1/4" SCHEDULE 40 PIPE WITH REINFORCED ENDS
12. ESTIMATED LT WT — 94,600 POUNDS
13. CENTER OF GRAVITY — 81.35" LOADED
14. CURVE NEGOTIATIONS:
    MINIMUM RADIUS OF TRACK CURVATURE – HORIZONTAL CURVES:
    UNCOUPLED CAR — 180 FT
    COUPLED CAR (TANK ON CURVE, STANDARD CAR ON TANGENT) — 267 FT
    COUPLED CAR (STANDARD CAR ON CURVE, TANK ON TANGENT) — 156 FT
    COUPLED CAR(TWO LIKE CARS) — 270 FT

    MINIMUM RADIUS OF TRACK CURVATURE – VERTICAL CURVES:
    UNCOUPLED CAR — 652 FT
    COUPLED CAR (TANK CAR ON CURVE, STANDARD CAR ON TANGENT OR TWO LIKE CARS) — 780 FT

REV	BY	DATE	REVISION
B	KFC	6-9-98	ADD NOTE 10, REV TOP PLATFORM
A	KFC	2-2-98	UPDATE NOTES 9 AND 12

A.A.R. APPLICATION NO. L986049A

FILE:

TOLERANCES: UNLESS OTHERWISE SPECIFIED ON THIS DRAWING THE FOLLOWING TOLERANCES SHALL APPLY SEE D-145000 FOR ADDITIONAL TANK CAR TOLERANCES. FRACTIONS MACHINED ±1/64" (.016") ALL OTHERS: (1" to 2")±1/16", (2" to 10")±1/8", (10" to 20")±1/4", (OVER 20")±1/2"
DECIMALS 3 PLACE ±.005 2 PLACE ±.03 1 PLACE ±.1
ANGLES MACHINED ±1/2 DEG. ALL OTHERS ±1 DEG.

TRINITY INDUSTRIES, INC.
RAILCAR DIVISION

THIS DRAWING CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION OF TRINITY INDUSTRIES, INC. THE DRAWING IS THE PROPERTY OF TRINITY INDUSTRIES, INC. AND IS LOANED FOR ENGINEERING REVIEW ONLY. THE DRAWINGS MAY NOT BE COPIED OR USED FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN CONSENT OF TRINITY INDUSTRIES, INC. AND SHALL BE RETURNED ALONG WITH ALL COPIES UPON DEMAND. © TRINITY INDUSTRIES, INC. 1998

DRAWN	DLB	4-10-96
CHKD	KFC	4-29-96
APPD	MSR	5-1-96
1st FILE		95134
NLA		
WEIGHT		

GENERAL ARRANGEMENT

23,568 GAL, 4 COMPARTMENT
99" ID, STB, C & I
DOT 111A100W1 / AAR 211A100W1

DRAWING NO: D-40957 | SHEET 1 OF 1 | REV B | SIZE D